

Super-class electric-powered pressure washer

Cold water power for commercial applications





Cold Water | Electric Powered | Direct Drive



HD super class

Kärcher's super-duty class of cold water pressure washers are compact and highly mobile - yet pack a big punch - delivering up to 4.5 GPM at 3200 PSI. Designed for tough continuous-duty applications, they're the perfect choice for the demanding requirements of the construction, agriculture, and municipal services industries.

The HD super class features Kärcher's patented 4-pole water cooled motor and industrial axial pump design along with unique user-friendly features such as on-gun variable water flow control, complete trigger shutoff, and convenient triple changeover nozzle. The upright design and pneumatic wheels make for easy transport and quick storage.



1 Powerful and durable

- Robust, three-piston axial pumps features detergent-resistant brass cylinder head and stainless valves; pumps is protected by pressure switch and overflow valve.
- Built-in motor protection against voltage fluctuations and excessive temperatures
- Single-phase unit features ground-fault circuit interrupter (GFCI) for operator safety
- Low-speed, 4-pole, air-cooled motor runs quieter and cooler than conventional motors thus prolonging its service life
- Ceramic-coated piston.

2 Smart features

- Rear cable/hose rack provides added convenience.
- Kink-free, 33-ft. high-pressure hose is easy to wind, with integrated connection inside the gun which swivels under full pressure.
- Integrated lance holder for easy transport.
- Parking position for short breaks.

3 Outstanding mobility

- Large wheels for uneven surfaces.
- Upright design for easy, ergonomic transport.
- Integrated tilting aid at the rear.

Technical Data and Equipment

HD 3.5/30-4S Ea

HD 3.7/22-4S Eg

HD 4.5/32-4S Eb

HD 4.5/32-4S Ec

- 4-pole water-cooled motor
- Features Kärcher power nozzle
- Pneumatic tires
- Easy Press trigger gun with soft grip



Technical Data

| | | | | | |
|------------------------|--------|----------------|----------------|---------------|---------------|
| GPM | | 1.8-3.5 | 1.8-3.7 | 2.2-4.5 | 2.2-4.5 |
| PSI | | 435-3000 | 435-2200 | 435-3200 | 435-3200 |
| HP | | 9 | 6.9 | 10 | 10 |
| Electrical | | 220-240V / 1ph | 200-208V / 1ph | 230V / 3ph | 460V / 3ph |
| Amps | | 30 | 30 | 30 | 16 |
| Pump | | Kärcher Axial | Kärcher Axial | Kärcher Axial | Kärcher Axial |
| Ship Weight | lbs. | 168 | 158 | 182 | 182 |
| Dimensions (L x W x H) | inches | 22 x 20 x 43 | 22 x 20 x 43 | 22 x 20 x 43 | 22 x 20 x 43 |
| Color | | ■ | ■ | ■ | ■ |
| Order No. | | 1.286-127.0 | 1.286-115.0 | 1.286-128.0 | 1.286-129.0 |



makes a difference

Your Authorized Kärcher Professional Dealer:

Kärcher Commercial
Phone 888-805-9852
Fax 800-248-8409
info@karchercommercial.com
www.karchercommercial.com