

AIR COMPRESSORS

80 & 120-Gallon Two Stage Electric



Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Oil level sight indicator

Frame

- ✓ Powder coated ASME coded 80 or 120-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ Totally enclosed heavy-duty belt guard

Components

- ✓ ASME safety valves
- ✓ Pressure gauge
- ✓ Intake filter/silencer
- ✓ Tank shut-off valve

AES-23315-120HM

HORIZONTAL MODELS										
MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
ACS-23105-80HM	18.0 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	615 lb.	544 lb.
ACS-23175-80HM	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	52x26.5x53in.	20.75x23.5in.	780 lb.	709 lb.
ADS-23110-120HM	34.2 @ 175	10.0 HP, 230V, 1Ø, 39.0A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	890 lb.	811 lb.
AES-23315-120HM	46.5 @ 175	15.0 HP, 230V, 3Ø, 38.0A	Two stage	Cast iron	Splash lubricated cast iron	120-gallon	74x26.5x58in.	34.5x23.5in.	935 lb.	856 lb.

VERTICAL MODELS										
MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
ACS-23105-80VM	18.0 @ 175	5.0 HP, 230V, 1Ø, 23.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	695 lb.	544 lb.
ACS-23175-80VM	23.5 @ 175	7.5 HP, 230V, 1Ø, 31.0A	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	33x25x73in.	15.63x15.63in.	780 lb.	709 lb.

Consult factory for availability of more M Series air compressor models and voltages.