


# CW PREMIUM SERIES

## COLD WATER ELECTRIC BELT DRIVE



The electric version of the CW Series is perfect for heavily-soiled commercial and industrial equipment that requires indoor cleaning.



CW-4004-1ME3 shown with optional 460V, 3-phase motor (CX-0057)

### Pump

- ✓ External bypass system allows more water into the system to protect from heat build-up
- ✓ Forged brass manifold
- ✓ Thermal relief valve
- ✓ Water filter with clear sleeve for screen inspection

### Motor

- ✓ Totally enclosed fan-cooled electric motor with thermal overload protection
- ✓ 10-foot power cord

### Frame

- ✓ Powder coated steel tube handles and base plate
- ✓ Totally enclosed powder coated belt guard

### Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated lance and trigger gun with safety lock-off

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	NOZZLE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 10, 32.0A	General	3-0202	Preset pressure	NEMA 6-50P	0°, 15°, 25° & 40°	36in.	46x28x30in.	345 lb.	333 lb.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 30, 20.0A or 8.0 HP, 460V, 30, 10.0A	General	3-0202	Preset pressure	NEMA L15-30P	0°, 15°, 25° & 40°	36in.	46x28x30in.	255 lb.	243 lb.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 10, 32.0A	General	3-0202	Preset pressure	NEMA 6-50P	0°, 15°, 25° & 40°	36in.	46x28x30in.	350 lb.	338 lb.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 30, 20.0A or 8.0 HP, 460V, 30, 10.0A	General	3-0202	Preset pressure	NEMA L15-30P	0°, 15°, 25° & 40°	36in.	46x28x30in.	330 lb.	318 lb.
CW-3005-0ME1	3000	4.8	10.0 HP, 230V, 10, 41.5A	General	3-0202	Preset pressure	NEMA 6-50P	0°, 15°, 25° & 40°	36in.	45.5x32.5x30in.	470 lb.	396 lb.
CW-3005-0ME3*	3000	4.8	10.0 HP, 230V, 30, 26.0A or 10.0 HP, 460V, 30, 13.0A	General	3-0202	Preset pressure	NEMA 15-50P	0°, 15°, 25° & 40°	36in.	45.5x32.5x30in.	450 lb.	376 lb.
CW-4004-1ME3*	4000	3.9	15.0 HP, 230V, 30, 40.0A or 15.0 HP, 460V, 30, 20.0A	General	3-0075	Mi-T-M, preset pressure	NEMA 15-50P	0°, 15°, 25° & 40°	48in.	45.5x32.5x30in.	505 lb.	431 lb.
CW-5004-0ME3*	5000	4.0	15.0 HP, 230V, 30, 40.0A or 15.0 HP, 460V, 30, 20.0A	General	3-0261	Preset pressure	NEMA 15-50P	0°, 15°, 25° & 40°	48in.	45.5x32.5x30in.	505 lb.	431 lb.

\*460V motors available as options.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0057	460V, 3-phase models	CW-4004-1ME3 & CW-5004-0ME3
AW-8400-0021	Low pressure detergent injector	All models	CX-0062	460V, 3-phase model	CW-3005-0ME3
CX-0003	460V, 3-phase models	CW-2405-4ME3 & CW-3004-4ME3	CX-0093	Stationary option	CW-2405 & CW-3004 models
CX-0005	Insulated dual lance	All models	CX-0094	Stationary option	CW-3005, CW-4004 & CW-5004 models