

# CW PREMIUM SERIES

## COLD WATER GASOLINE BELT DRIVE



Built for industrial cleaning jobs, the CW Premium Series is deemed the workhorse of the industrial cold water pressure washer line.



CW-3504-5MGH

### Pump

- ✓ External bypass system allows more water into the system to protect from heat build-up
- ✓ Forged brass manifold (Nickel plated brass on 4000-PSI models)
- ✓ Thermal relief valve
- ✓ Water filter with clear sleeve for screen inspection

### Frame

- ✓ Powder coated steel tube handles and base plate
- ✓ Two-piece belt guard with 1/4-turn release

### Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated trigger gun with safety lock-off

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH	2500	4.4	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH	3000	3.5	389cc Honda OHV	General	3-0202	Preset pressure	0°, 15°, 25° & 40°	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH	3500	3.8	389cc Honda OHV	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGS	3500	3.8	404cc Subaru OHC	General	3-0203	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH	4000	3.5	389cc Honda OHV	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MVO	4000	4.0	480cc Vanguard OHV, electric start (battery included)	General	3-0075	Mi-T-M, preset pressure	0°, 15°, 25° & 40°	48in.	46x28x30in.	330 lb.	256 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0045	Electric start (battery included)	CW-3504 & CW-4004 Honda models
AW-8400-0021	Low pressure detergent injector	All models	CX-0054	Roll cage	All Honda models & CW-3504-5MGS
CX-0005	Insulated dual lance	All models	CX-0055	Roll cage	CW-4004-5MVO