


# GENERATORS

## 3000, 4000 & 5000-Watt Gasoline



This portable generator provides dependable power for homeowners seeking a reliable electrical backup and is powerful enough for most industrial and contractor needs.



### Alternator

- ✓ Total harmonic distortion (THD) less than 5%
- ✓ 100% copper windings

### Frame

- ✓ Heavy-duty wraparound frame with 1-inch steel tubing
- ✓ Angled isolator design features four neoprene isolators

### Components

- ✓ Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- ✓ Large low-tone mufflers
- ✓ Heavy-duty industrial air cleaners

### Miscellaneous

- ✓ USDA/USFS-approved spark arrestors

MODEL NUMBER	GEN-3000-1MH0	GEN-4000-OMS0*	GEN-5000-OMH0 / GEN-5000-OMK0 / GEN-5000-OMS0
MAX. AC OUTPUT	3000 watts	4000 watts	5000 watts
RATED AC OUTPUT	2450 watts	3500 watts	4400 watts
DISPLACEMENT/ENGINE	163cc Honda OHV	211cc Subaru OHC	270cc Honda OHV / 277cc Kohler OHV / 287cc Subaru OHC
ALTERNATOR	Brushless 120V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	25.0	33.3/16.7	41.7/20.8
CONT. AMPS (120V/240V)	20.4	29.2/14.6	36.7/18.3
RECEPTACLES	(1) 120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(1) 20A push-button	(2) 20A toggle circuit breaker, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	74.8	75.7 / 74.0	73.8
FUEL CAPACITY	2.6 gallons, large capacity tank	5.7 gallons	5.7 gallons
RUN TIME (AT FULL LOAD)	7.4 hours	9.3 hours	6.8 hours
FUEL SHUT-OFF VALVE	Yes	Yes	Yes
FUEL GAUGE	No	Yes, easy-to-read	Yes, easy-to-read
FULL POWER SWITCH	No	Yes	Yes
DIMENSIONS (LxWxH)	25x18x18in.	29x19.75x22.5in.	29x19.75x22.5in.
SHIP WT.	146 lb.	168 lb.	198 lb.
NET WT.	130 lb.	146 lb.	176 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

\*EPA compliant in 49 states. Not to be sold in California.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	4000 & 5000-watt models	AW-5740-0009	Wheel kit	4000 & 5000-watt models
AW-5090-0003	Lifting hook	4000 & 5000-watt models	GX-0004	Hour meter	4000 & 5000-watt models