

JP SERIES

COLD WATER GASOLINE DIRECT DRIVE



The JP Series features a 1-inch steel extended handle design for excellent balance and mobility.



JP-3504-3MSB

Pump

- ✓ Forged brass manifold
- ✓ Thermal relief valve
- ✓ In-line water strainer

Frame

- ✓ Powder coated steel tube handles and base plate

Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated trigger gun with safety lock-off

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	MI-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB	2400	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2403-3MSB	2400	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MSB	2700	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MSB	3000	3.0	265cc Subaru OHC	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MSB	3500	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MSB	4000	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models
AW-8400-0021	Low pressure detergent injector	All models
CX-0005	Insulated dual lance	All models

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0083	External bypass system	2400 to 2700-PSI models
CX-0084	External bypass system	3500 to 4000-PSI models