

CD SERIES

COLD WATER ELECTRIC DIRECT DRIVE



Designed for all-purpose cleaning, the lightweight CD Series are ideal for homeowners and small industrial jobs. This electric model is perfect for applications where exhaust fumes are prohibited.



CD-1002-2MUH

Pump

- ✓ Forged brass manifold
- ✓ Thermal and safety relief valves
- ✓ Adjustable low pressure detergent injector

Motor


- ✓ Totally enclosed fan-cooled electric motor with thermal overload protection
- ✓ 35-foot, 15-amp power cord (20-amp on CD-1502 models) with ground fault circuit interrupter (GFCI)

Frame

- ✓ Powder coated steel mounting plate with center balanced lift and four rubber isolators

Unit Includes:

- ✓ 25-foot x 3/8-inch non-marking hose with quick connects
- ✓ Insulated lance and trigger gun with safety lock-off



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	NOZZLE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CD-1002-3MUH	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	AR	3-0362	Adjustable pressure	NEMA 5-15P	Variable high/low pressure	36in.	20x11.5x14in.	70 lb.	58 lb.
CD-1002-2MUH*	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	General	3-0278	Adjustable pressure	NEMA 5-15P	15° high/low pressure	36in.	20x11.5x14in.	71 lb.	66 lb.
CD-1502-3MUH	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	Variable high/low pressure	36in.	20x11.5x14in.	76 lb.	70 lb.
CD-1502-2MUH*	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	15° high/low pressure	36in.	20x11.5x14in.	76 lb.	70 lb.

*Pump accepts incoming water up to 175°F.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
18-0370	Rotating nozzle	CD-1502 models	50-0161	High pressure detergent injector	All models
18-0371	Rotating nozzle	CD-1002 models	CX-0030	50-foot high pressure hose	All models