

CWC PREMIUM SERIES

COLD WATER GASOLINE BELT DRIVE



As one of the most powerful cold water pressure washers on the market today, this unit is jobsite ready with a 1¼-inch roll cage, handles and lifting hook.



CWC-5004-4MAH

Pump

- ✓ Forged brass manifold
- ✓ Thermal and safety relief valves
- ✓ Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-4MGH)

Frame

- ✓ Industrial frame design includes powder coated steel frame with 1¼-inch roll cage, handles and lifting hook
- ✓ Two-piece belt guard with ¼-turn release
- ✓ Locking tire brake

Components

- ✓ Fuel tank is powder coated outside and zinc-plated inside to prevent rusting
- ✓ 13.0-gallon fuel tank capacity for 9.5 hour running time

Unit Includes:

- ✓ 50-foot x ¾-inch non-marking hose with quick connects (½-inch hose on CWC-3008-4MGH)
- ✓ Insulated trigger gun with safety lock-off

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CWC-3008-4MGH	3000	8.0	688cc Honda OHV, electric start (battery included)	General	3-0279	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-5004-4MAH	5000	4.0	688cc Honda OHV, electric start (battery included)	AR	3-0213	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5004-4MGH	5000	4.0	688cc Honda OHV, electric start (battery included)	General	3-0261	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5005-4MGH	5000	5.0	688cc Honda OHV, electric start (battery included)	General	3-0262	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-6004-4MGH	6000	3.7	688cc Honda OHV, electric start (battery included)	General	3-0261	Preset pressure	0°, 15°, 25° & 40°	48in.	43x27.75x36in.	531 lb.	408 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-3000-0035	Sand injector	CWC-5004 & CWC-6004 models
AW-7500-0035	Rotating nozzle	CWC-5004 & CWC-6004 models